HIKVISION°



36.5° C

Temperature Screening Thermal Solutions

I SAFER, FASTER, SMARTER

With advanced detectors and algorithms, Hikvision's Temperature Screening Thermal Cameras can detect elevated skin-surface temperatures in moving crowds such as passengers, commuters and shoppers, with accuracy up to $\pm 0.3^{\circ}$ C.





Increased Safety NON-CONTACT measurement





High Efficiency

ONE SECOND to detect the skin-



Multi-Person Detection SIMULTANEOUSLY captures





Temperature Screening Thermal Products

DS-2TD2637B-10/P

DS-2TD2636B-15/P





- 384*288 thermal resolution
- 10 / 15 mm thermal lens Recommended camera-target distance: 3-9 m
- 6 mm optical lens

DS-2TD2617B/PA



Al Detection

- 160*120 thermal resolution
- 3 / 6 mm thermal lens Recommended camera-target distance: 0.8-1.5 m / 1.5-3.0 m
- 4 / 6 mm optical lens

DS-2TD1217B/PA



Al Detection

- 160*120 thermal resolution
- 3 / 6 mm thermal lens Recommended camera-target distance: 0.8-1.5 m / 1.5-3.0 m
- 4 / 6 mm optical lens

DS-2TP21B-6AVF/W



- 160*120 thermal resolution
- Max 8 MP optical resolution
- 6 mm thermal lens Recommended camera-target distance: 1.5-3.0 m

ISD-SMG318LT-F

Metal Detector Door with Thermal Turret Camera

- LCD screen with real-time temperature display and people-counting statistics
- Light and sound alarm
- 160*120 thermal resolution
- 3 mm lens / 4 mm optical lens

DS-2TE127-G4A



Blackbody Calibrator

 Increases the temperature measurement accuracy from ±0.5° C to ±0.3° C.